First Flex—Long Life Smooth Bore Heavy Duty

DOUBLE-HELIX WIRE REINFORCEMENT

VOL-U-FLEX Line and Port Hose feature a double-helix spring-steel wire reinforcement encapsulated in a continuous bridge of rubber for tough, long-life service. This unique Salem-Republic feature greatly extends hose life at a cost comparable to what you would expect to pay for conventional constructions.





Heavy Duty Line Hose (V6339-6768D-D1201)

TUBE 1/8" static-conducting NR/SBR.

CARCASS Multi-plies of high-tensile square-woven polyester fabric. Dual high-tensile steel wire helix.

COVER Weather, ozone and abrasion-resistant SBR.

ENDS Plain cut or soft cuffs

INSIDE DIAMETER	OUTSIDE DIAMETER	APPROX. WT./FT.	MIN. BEND RADIUS
* 4.00"	4.60"	2.19	8.0"
5.00"	5.70"	3.16	11.0"
* 6.00"	6.74"	4.39	14.0"
* 8.00"	8.80"	6.70	18.0"
10.00"	10.84"	8.53	22.0"
12.00"	12.90"	10.40	27.0"

Special ends available upon request.

Special Extra H.D. Hose For Vactor Trucks

(V6109-6768D-D2598)

TUBE Full 1/4" NR/SBR.

CARCASS One-ply high-tensile spun polyester woven fabric and special design dual high-tensile steel wire helix for increased flexibility.

COVER Weather, ozone and abrasion-resistant SBR.

ENDS Soft cuffs

INSIDE DIAMETER	LENGTH	WEIGHT/ LENGTH
8	62"	40#
* 8	66"	44#
8	120"	80#
* 8	127"	85#
8	192"	136#
8	240"	160#
6	120"	55#
10	120"	105#
12	120"	125#

*Denotes stocked items.

Contact us for your special length requirements.

All vacuum hose, including leaf collector, are available in food-grade compounds.

^{*}Denotes stocked items.